

CDC Recommendations	Fridge-tag® 2 Status	Comments
LED Display: current temp	YES	
LED Display: high & low temps	YES	30 days High/Low on screen
LED Display: Hi/Low Alarm status	YES	Alarm Status & Alarm checked status
Continuous Temp. Monitor (Minimum: 1 reading every 15 minutes)	YES	Every 1 minute 60 readings/hour 1440 reading/day FULL CONTINUOUS
Memory: 4000 readings Est. 39 days @ 15 min.	YES	43,200 readings/mo 86,400 / 60 days FULL CONTINUOUS
Device Stops or Memory is reset after download	NO	NO NEED TO RESET History automatically erased after 60 days
Operating range -20°C to +40°C	YES	-30°C to +50°C
Uncertainty: +/- 0.5°C	YES	
Resolution: +/- 1.0°C	YES	
Battery Life: 6 months	YES	24 months
Track technicians reading temps. twice daily	YES	Use of READ button documents technician interaction
Download data via USB & standard computer	YES	NO Software No cradle No wire
Report: show alarm configurations; high & low temps & time outside of the high/low thresholds	YES	
Data export capability: Excel, CSV, Txt	YES	Device creates a PDF & Txt file now
Detachable temperature probe, liquid fill vial, 1m cable	YES	THIN – Ribbon wire fits between gasket

Source: CDC website – Guidelines for Storage and Temperature Monitoring of Refrigerated Vaccines

Distributed By MicroDAQ, LLC 603-746-5524 www.MicroDAQ.com